

OASIS

Tough outside, cool inside.
The only truck refrigeration unit specially designed to meet the challenges raised by high ambient









High capacity truck refrigeration range Oasis has been designed to meet the challenges raised by high ambient temperatures up to +50°C.



OASIS

HIGH REFRIGERATION CAPACITY

In high ambient climates, sustaining the cold chain is more important than anywhere else. The Oasis range featuring R404A and R134A refrigerants delivers unmatched capacity and constant airflow, especially thanks to its electrical fans. Truck operators can depend on reliable protection of perishables.

HIGH AMBIENT DESIGNED

Durability: combining aerodynamic styling and reliability, the OASIS range has been designed with rugged and durable material to resist harsh conditions. All components have gone through UV and chemicals resistance tests to operate in extreme climates.

Easy start: the new alternator design enables the engine to reach its nominal speed with fewer loads by delaying the power output. This feature helps to extend the lifecycle of key internal components such as the engine, clutch and belts.

AVAILABLE IN MULTI-TEMPERATURE

The Oasis range offers flexibility for multi-product deliveries with 7 standard configurations available thanks to the ultra-slim evaporator range.

MAINTENANCE FRIENDLY OPERATION

Accessibility and safety are enhanced on the OASIS range: handling bars, lateral door screw locking system and main shutoff switch. Service inspections and routine maintenance are operated quicker and safer.

MONO-TEMPERATURE CONFIGURATIONS

	REFRIGERATION CAPACITY (WATTS)* ROAD		HEATING CAPACITY -18°C/18°C (W) STANDBY		AIRFLOW (m³/h)	WEIGHT INCL. EVAPORATOR
	0°C/30°C	-20°C/30°C	0°C/30°C	-20°C/30°C		(kg)
OASIS 350	10300	6400	9600	5800	2770	596
OASIS 330	7820	5370	6620	4850	2909	626
OASIS 260	6360	3920	5490	2870	2500	429
OASIS 250	5800	3600	4440	2840	2250	429
OASIS 250 Fresh	5030	n/a	1430	n/a	2250	429
OASIS 150	5000	2600	4070	2000	2250	391
OASIS 150 Fresh	3310	n/a	2950	n/a	1590	340

MULTI-TEMPERATURE CONFIGURATIONS

	CAPACITY (Watts)* -20°C	AIRFLOW (m³/h)	WEIGHT W/O EVAPORATOR (kg)	BOXES CONFIGURATION
OASIS 350 MT°	6200	Up to 4500**	566	3
OASIS 250 MT°	3600	1500	411	4

^{*} Ambient temperature at +30°C (per A.T.P. procedure) ** According to evaporator type




The Oasis range benefits from the EasyCOLD microprocessor.

ACCESSORIES

- Battery
- Battery box
- Fuel tank 90 or 200 L
- · Plunger tube for vehicle fuel tank
- Automatic phase reverser
- Datacold 300 or 600
- · Oil drain extension
- Control panel & cable extension
- · Waterproof box for cab command
- Door switch
- Lynx™ Fleet

EXAMPLE OF CONFIGURATIONS OASIS 250 MT



EXAMPLE OF CONFIGURATIONS OASIS 350 MT









